Checklist for straps

(or two ways to approach a strap project) ©Verlane Desgrange 2002

One way to make a simple strap project

- 1. Cut item out
- 2. Split leather to correct thickness
- 3. Prepare loop stock
 - 1. Cut out strip of leather
 - 2. Edge with edge tool (both Flesh side and Grain side)
 - 3. Dampen
 - 4. Slick
 - 5. Polish edges
 - 6. Seal edges with Resolene
 - 7. Allow to dry
- 4. Dampen main project
- 5. Slick
- 6. Round edges off on both flesh side and grain side with edge tool
- 7. Crease edges with creaser
- 8. Polish edges with edge burnisher or canvas cloth
- 9. Seal edges with Resolene
- 10. Allow to dry, making sure it does not curl as it dries
- 11. Punch buckle slots if needed
- **12.** Prepare for stitching
 - Lap skive buckle lap
 - Prepare thread length from unwaxed linen thread
 - 1. Cut to correct length
 - 2. Taper both ends of thread
 - 3. Wax with beeswax
 - 4. Thread needles (one on each end)
 - Roll buckle lap around buckle, grain side to grain side
 - Mark stitching with overstitcher
 - Tack damp loop length and lap down, from "backside", putting tacks in stitch marks
- 13. Stitch in hardware and loops
- 14. Block damp loop on loop iron
- 15. Crease damp loop while on iron
- 16. Set aside to dry
- 17. Punch holes

Another way to make the same project

- 1. Cut item out
- 2. Split leather to correct thickness

- 3. Round off edges with edge tool
- 4. Dampen
- 5. Slick
- 6. Crease edges
- 7. Polish edges
- 8. Seal edges with Resolene
- 9. Prepare loop stock
 - 1. Cut out strip
 - 2. Edge with edge tool
 - 3. Dampen
 - 4. Slick
 - 5. Polish edges
 - 6. Seal with Resolene
 - 7. Set aside to dry
- 10. Allow project to dry, making sure it does not curl in the process
- 11. Punch buckle slots
- 12. Lap skive buckle lap
- 13. Stitch in hardware and loops
- 14. Punch holes in strap from FS (reverse punch)